

The Jonell CarboPur R series filter cartridges flow from outside to inside direction. The JRF element is specifically designed for the removal of hydrocarbons through adsorption

The Jonell JRF is built robust with spot welded caps and a specially designed core to help prevent carbon from bypassing and flowing down stream. The carbon canister comes with two handles for an easier install and removal.

## Performance

| Micron Rating                   | N/A             |
|---------------------------------|-----------------|
| Recommended Initial DP          | < 2.0 psid      |
| Maximum Recommended Temperature | 120 °F          |
| Flow Direction                  | Outside to In   |
| Configuration I                 | Double Open End |

# ow Direction Outside to In Onfiguration Double Open End JR



JRF 1122-C-2.25 Filter Cartridges

### Materials

Core: Tin Plated Steel
Outer Core: Tin Plated Steel

**End Caps:** Electro Galvanized Steel

Gasket: Buna

#### Jonell 900 Industrial Pkwy P.O. Box 1092 Breckenridge Texas 76424 USA Telephone: 254-559-7591 Fax: 254-559-9863 sales@jonellinc.com



# **Dimensions**

| Length               | 22 inches       |
|----------------------|-----------------|
| Outside Diameter     | 11 inches       |
| Inside Diameter      | 2.25 inches     |
| Quantity             | 1 per box       |
| Approx. Shipping Wt. | 32 lbs. per box |
| Box Dimensions       | 12" x 12" x 24" |

<sup>\*</sup>Above dimensions are nominal in inches

# Visit us at www.Jonellinc.com

For questions about filtration applications, replacement needs or help troubleshooting process and filtration issues contact an approved JONELL representative.

<sup>\*</sup>For Custom Engineered Products and Solutions... Consult Factory