



A Filtration Group Company

JMG 36-R

The JMG 36-R elements are inside to outside flow direction elements specifically designed for gas filtration. Through the combination of a specialized Microglass fiber coalescing media in a varying scale of fiber diameters that has been known to help with challenging applications.

The Microglass filter media is supported with a heavy-duty, spiral locked steel core. Tinned steel end caps are then mechanically secured, to center core providing cartridge strength you can trust not to collapse or bypass when properly applied.

Performance

Standard Micron Rating	0.3 μ Liquids
Standard Micron Rating	0.3 μ Solids
Recommended Initial DP	< 0.5 psid
Recommended Change-Out DP	15 psid
Maximum Operating Temperature	300 °F
Collapse Pressure	> 75 psid
Flow Direction	Inside to Out
Configuration	Double Open End

Materials

Coalescing Media:	Microglass
Support:	Needled Polyester
Core:	Tinned Steel
End Caps:	Tinned Steel
Gaskets:	Buna-N

**For Custom Engineered Products and Solutions... Consult Factory*



JMG 36-R Filter Cartridges

Dimensions

Length	36
Outside Diameter	3.55
Inside Diameter	2.09
Flow Pattern	Inside to Out
Quantity	4 per box
Approx. Shipping Wt.	10 lbs. per box
Box Dimensions	7.25 x 7.25 x 36.25

**Above dimensions are nominal in inches*



900 Industrial Pkwy P.O. Box 1092
Breckenridge Texas 76424 USA
Telephone: 254-559-7591
Fax: 254-559-9863
sales@jonellinc.com

Visit us at www.Jonellinc.com

For questions about filtration applications, replacement needs or help troubleshooting process and filtration issues contact an approved JONELL representative.