

JPMX 4640-150AV-NCC

Liquid Filtration

The Jonell LiquiPleat X series filter cartridges have a range of efficiency, outside to inside flow direction elements specifically designed for the removal of solid contaminants in critical applications.

Jonell JPMX's are available in various grades of absolute rated high performance nomex media. While the element is typically designed with a coreless body, the options to customize the hardware is still available to suit your application.



JPMX 4640-150AV-NCC Filter Cartridges*

W: processtechnologies.filtrationgroup.com/en-US

ISO 9001:2015 Certified

For questions about filtration applications, replacement needs or help troubleshooting process and filtration issues contact an approved JONELL representative.

Performance

Standard Micron Rating	150 μ at 99.98% efficiency
Recommended Initial DP	< 2.0 psid
Recommended Change-Out DP	15-25 psid
Maximum Temperature	400° F
Flow Direction	Outside to In
Configuration	Single Open End

Materials

Media	Nomex
Core	None
End Caps	Tinned Steel
Supports	Epoxy Coated Screen
Gaskets	Viton

Dimensions

Length	40 inches
Outside Diameter	4.25 inches
Inside Diameter	1.8 inches
Quantity	4 per box

Dimensions are nominal in inches

** Picture is for illustrative purposes only. Actual product appearance may vary.*

JPMX 4640-150AV-NCC-0819