

JQC 343-FF-PMG-DD-SPL

Gas Filter

The Jonell GasPleat series filter cartridges are high efficiency filter elements specifically designed for the removal of solid particulate contaminants in critical applications.

The Jonell JQC is made with nylon end caps and metal components designed specifically for the demands of the oil and gas industry. The filtering media is then attached to the end caps and core via a highly resistant adhesive to prevent any possibility of by-pass. Tin plated steel outer cartridge encasements are designed to protect the element against erosion caused by high flow rates.



JQC 343-FF-PMG-DD-SPL Filter Cartridges*

W: processtechnologies.filtrationgroup.com/en-US

ISO 9001:2015 Certified

For questions about filtration applications, replacement needs or help troubleshooting process and filtration issues contact an approved JONELL representative.

Performance

Standard Micron Rating	0.3 μ at 99.98% efficiency
Recommended Initial DP	< 0.5 psid
Recommended Change-Out DP	15 psid
Maximum Temperature	275° F
Maximum DP	> 60 psid
Flow Direction	Outside to In
Configuration	Single Open End

Materials

Media	Microglass
Core	Tinned Steel
Support	Polyester Felt
End Caps	Nylon
Gaskets	Buna

Dimensions

Length	43 inches
Outside Diameter	4.5 inches
Inside Diameter	3 inches
Quantity	4 per box

Dimensions are nominal in inches

** Picture is for illustrative purposes only. Actual product appearance may vary.*

JQC 343-FF-PMG-DD-SPL -3/20