



A Filtration Group Company

JRF 1122-C-N

The JRF 1122-C-N carbon filter cartridges flow from outside to inside direction, the JRF element is specifically designed for the removal of hydrocarbons through adsorption

The JRF 1122-C-N is built robust with spot welded caps and a specially designed core to help prevent carbon from bypassing and flowing down stream. The carbon canister comes with two handles for an easier install and removal.

Performance

Micron Rating	N/A
Recommended Initial DP	< 2.0 psid
Maximum Recommended Temperature	120 °F
Flow Direction	Outside to In
Configuration	Double Open End



JRF 1122-C-N Filter Cartridges

Materials

- Core:** Tin Plated Steel
- Outer Core:** Carbon Steel
- End Caps:** Electro Galvanized Steel
- Gasket:** Buna

**For Custom Engineered Products and Solutions... Consult Factory*

Jonell
900 Industrial Pkwy P.O. Box 1092
Breckenridge Texas 76424 USA
Telephone: 254-559-7591
Fax: 254-559-9863
sales@jonellinc.com

Dimensions

Length	22.2 inches
Outside Diameter	10.8 inches
Inside Diameter	1.5 inches
Quantity	1 per box
Approx. Shipping Wt.	32 lbs. per box
Box Dimensions	12" x 12" x 24"

**Above dimensions are nominal in inches*

Visit us at www.Jonellinc.com

For questions about filtration applications, replacement needs or help troubleshooting process and filtration issues contact an approved JONELL representative.

